



Switch di rete

Switch di rete industriale su barra DIN con 4 porte 10/100Mbps, porta 1 con Hi-PoE 60W max, 1 porta 1.000Mbps, 1 porta SFP, 4 porte PoE autosensing, funzione Extended Poe fino a 250 mt con telecamere Pixvideo con cavo cat.5E/6, alimentazione 53Vdc (totale massimo 60W), funzione Watchdog. Con alimentatore in dotazione. Supporta il backup a doppia alimentazione. (152.0x110.4x30.0mm)

CARATTERISTICHE TECNICHE

Technical Specification

Model	ACE052PD
General	
Ethernet Port	1*100/1000 Base-X 1*10/100/1000 Base-T 4*10/100 Base-T (PoE power supply)
PoE Power Consumption	Port1≤60W, Port2-4≤30W, Total≤60W
PoE PIN Assignment	1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
POE Power Management	Support
PoE Protocol	IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
Switching Capacity	6.8G
Packet Forwarding Rate	3.57Mpps
Packet Buffer Memory	1Mb
MAC Table size	8K
Flow Control	Enable by default
Application Humidity	5%~95%
Power	DC 48~57V power adapter
Lightning Protection	Common Mode 6KV Differential Mode 4KV
Working Temperature	Air Discharge 15KV Contact Discharge 8KV
Working Temperature	-30°C~65°C
Weight	440g
Dimension	150mm×108mm×30mm