




Tastiera di controllo

Tastiera di controllo per NVR, DVR, NVT, NVX e Speed dome con Joystick a 3 assi. Con display LCD, seriale RS485 per controllo speed dome, seriale RS232 per controllo DVR e porta ethernet 10/100 Mps per controllo di speed dome IP e DVR via rete LAN, alimentatore in dotazione, 12Vdc, 2A (330.0 x 139.0 x 53.0mm)

PIXVIDEO



CARATTERISTICHE TECNICHE

Technical Specification

| | |
|--|---|
| Model | ACE101 |
| General | |
| Keyboard Key panel | Electromechanical |
| Joystick | 3-axis, vector-solving, with twisting, return to-center head |
| Keyboard Connector | RJ-45, RS232, RS485, RS422 (reserved), USB |
| Keyboard Communication | Direct Mode, Network Mode |
| Direct Mode | Interface: 1 RS232/2 RS485 DVR Protocol: DH-2 Dome Protocol: DH-SD1/PELCO-D/PELCO-P, etc |
| Network Mode | Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol |
| Display | LCD, 75.2mm×33.85mm |
| Maximum Number of Users | 64 (including "admin") |
| Max RS485 Addresses (Each User) | 256 |
| Max Number of PTZ (IPC) That Can be Added over Network (Each User) | 2048 |
| Environmental | |
| Power Supply | Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/2A |
| Power Consumption | 5W |
| Working Temperature | -10°C~+55°C |
| Working Humidity | 10% ~ 90% |
| Atmosphere Pressure | 86kpa~106kpa |
| Dimension | 330mm×139mm×53mm (W×D×H)(height: 103mm including joystick) |
| Weight | 1.3kg (Including package) |