

PIX-ACE705

3-Port PoE Extender with 2-Port PoE Out and 1-Port PoE In



- Support passive PoE cascade power supply and Ethernet data exchange
- Support IEEE 802.3af/at standard power supply IP Camera
- Cooperate with High PoE Midspan (PIX-ACE042A), able to cascade level 2 PoE Extender, connect to 3 IPC (total power consumption $\leq 25W$), max transmission distance 300m
- 1*RJ45 10/100M PoE power supply input; 1*RJ45 10/100M supply power for IP Cam; 1*RJ45 10/100M supply power for the next extender
- Installation mode: junction box internal mounting, DIN railmounting

PIXVIDEO
image without compromises

TECHNICAL SPECIFICATION

Model	PIX-ACE705
Ethernet Port	1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC
Transmission Distance	Cooperate with PIX-ACE042A, able to cascade level two extender, connect to 3 IPC (level one extender connects to 1 IPC, the OUT port of level two extender and CAMERA port connect to 1 IPC respectively, total power consumption $\leq 25W$), transmission distance is 300m
Power Consumption	$\leq 3W$
Application Humidity	10%~90%
Working Temperature	- 30°C~65°C
Weight	57g
Dimension(W×D×H)	79mm×52mm×23mm

Application

